

No.235DOC-0132

Doc No. D3B042 D5B067

EU Declaration of Conformity

Identification of the Product ϕ 22 Emergency Stop SwitchesName and address of ManufacturerName and address of the authorized representative :

IDEC CORPORATION APEM SAS

2-6-64 Nishimiyahara, Yodogawa-Ku, 55, Avenue Edouard Herriot BP1, 82303

Osaka 532-0004 Japan Caussade Cedex, France

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration : Series Name – YW Series

Model No. – Details are as per attached sheet

The object of the declaration described above is in conformity with the relevant EU harmonization

legislation:

2014/35/EU Low Voltage Directive 2006/42/EC Machinery Directive

2011/65/EU and (EU)2015/863 Restriction of the use of certain hazardous substances

(RoHS) Directive

Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.

EN 60947-5-5/A2:2017 EN IEC 63000: 2018

Where applicable, the notified body

Additional Information:

Signed for and on behalf of the above named manufacturer:

Place and date of issue: Japan, 20 April, 2016

Japan, 18 November, 2021 (Revised)

Name, function : Masaki Tsuri, Executive Officer

Quality Assurance Center

Signature :

masahi Iswa



No.235DOC-0132

	D2B106
Doc No.	D3B042
	D5B067

20 April, 2016 1 April, 2018 (Revised) Page 1 of 2

YW Series Type Designation

 $\frac{YW}{1}$ $\frac{1}{2}$ $\frac{L}{3}$ - $\frac{V}{4}$ $\frac{4}{5}$ $\frac{E}{6}$ $\frac{1}{7}$ $\frac{1}{8}$ $\frac{Q}{9}$ $\frac{3}{10}$ $\frac{R}{11}$ $\frac{*******}{12}$

- 1. YW Series
- 2. Configuration
 - 1 Round
 - 4 Round with Metal Ring
- 3. Operator Function
 - B Non-Illuminated
 - L Illuminated
- 4. Function
 - V Push-Lock-Turn-Reset or Pull-Reset
- 5. Button Style (May be followed)
 - 1 Flush
 - 2 Extended
 - 4 Mushroom
 - F2 Extended (With Full Shroud)
- 6. Terminal Configuration (May be followed)
 - E Screw Terminal
- 7. NO Contact Arrangement (May be followed)
 - 0 None
 - 1 1 NO Contact
 - 2 2 NO Contacts
 - 3 3 NO Contacts
 - 4 4 NO Contacts
 - 5 5NO Contacts
 - 6 6NO Contacts



No.235DOC-0132

	D2B106
Doc No.	D3B042
	D5B067

20 April, 2016 1 April, 2018 (Revised) Page 2 of 2

- 8. NC Contact Arrangement (May be followed)
 - 0 None
 - 1 1 NC Contact
 - 2 2 NC Contacts
 - 3 3 NC Contacts
 - 4 4 NC Contacts
 - 5 5 NC Contacts
 - 6 6 NC Contacts
- 9. Input Style (May be followed)
 - Q Direct

Blank - Non-illuminated

10. Lamp Voltage (May be followed)

Blank - Non-illuminated

- 0 None
- 2 LED Lamp, Rated 6V ac/dc, 0.5W
- 3 LED Lamp, Rated 12V ac/dc, 0.5W
- 4 LED Lamp, Rated 24V ac/dc, 0.5W
- 5 Incandescent Lamp, 6.3V, 1W
- 6 Incandescent Lamp, 18V, 1W
- 7 Incandescent Lamp, 30V, 1W
- H LED Lamp, Rated 100/120V ac/dc, 2W max.
- H2 LED Lamp, Rated 100/110V ac/dc, 2W max.
- M LED Lamp, Rated 200/220V ac/dc, 3W max.
- M3 -LED Lamp, Rated 200/240V ac/dc, 3W max.
- M4 -LED Lamp, Rated 230/240V ac/dc, 3W max.
- 11. Button Color (May be followed)

One or Two letters denoting color

12. Additional letter(s) and/or number(s) (May be followed)