



No.235DOC-0101

Doc No.	D2B128
	D3B029
	D5B135

EU Declaration of Conformity

Identification of the Product	Safety Switch
Name and address of Manufacturer IDEC CORPORATION 2-6-64 Nishimiyahara, Yodogawa-Ku, Osaka 532-0004 Japan	Name and address of the authorized representative : APEM SAS 55, Avenue Edouard Herriot BP1, 82303 Caussade Cedex, France

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration :

Series Name – HS5D Series
Model No. – Details are as per attached sheet

The object of the declaration described above is in conformity with the relevant EU harmonization legislation :

2014/35/EU	Low Voltage Directive
2006/42/EC	Machinery Directive
2011/65/EU and (EU)2015/863	Restriction of the use of certain hazardous substances (RoHS) Directive

Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.

EN 60947-5-1:2017
GS-ET-15:2019
EN IEC 63000:2018

Where applicable, the notified body

Additional Information :

Signed for and on behalf of the above named manufacturer :

Place and date of issue :	Japan, 20 April, 2016 Japan, 20 October, 2021 (Revised)
Name, function :	Masaki Tsuru, Executive Officer Quality Assurance Center
Signature :	

Masaki Tsuru

Doc No.	D2B128
	D3B029
	D5B135

20 April, 2016
 1 April, 2018 (Revised)
 Page 1 of 1

HS5D Series

HS5D - 11 R Z xx P -*****
 (1) (2) (3) (4) (5) (6) (7)

- (1) Series HS5D
- (2) Contact configuration
 - 11: 1NO+1NC contacts
 - 02: 2NC contacts
 - 12: 1NO+2NC contacts
 - 03: 3NC contacts
- (3) Operating direction of actuator
 - Blank: Actuator inserted from the top and front
 - R: Actuator inserted from the top and right
 - L: Actuator inserted from the top and left
 - B: Actuator inserted from the top and back
- (4) Actuator cover type
 - Blank: Polymeric cover
 - Z: Zinc die-cast cover
- (5) Actuator cover color and Body color
 - xx: Any two letters specify the color
- (6) Conduit
 - Blank: Threaded as per G 1/2 under JIS B 0202
 - P: Threaded as per PG 13.5 under DIN 40430
 - M: Threaded as per M20 under IEC 60423
 - C: Connector complied with IEC/EN 61076-2-101
 - C1: 5 Pin Connector complied with IEC/EN 61076-2-101 *1
- (7) Additional letters and/or numbers (may be followed)
 - ***** : Manufacturer Control No.

*1 In the case that (6) Conduit is “C1”, (2) Contact configuration is “11” or “02”.