

## NRNT8.E59804 - Switches, Industrial Control Certified for Canada - Component

\*\*HISTORICAL\*\*

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <a href="https://www.ul.com/about/locations">https://www.ul.com/about/locations</a>.

## Switches, Industrial Control Certified for Canada - Component

See General Information for Switches, Industrial Control Certified for Canada - Component

IDEC CORP E59804

1175 ELKO DR SUNNYVALE, CA 94089 USA

## Investigated to CAN/CSA C22.2. No. 14-10

**Open type for use in industrial applications** Model(s) RV1H-G-D12, RV1H-G-D18, RV1H-G-D24, RV1H-G-D48, RV1H-G-D5, RV1H-G-D6, RV1H-G-D60, RV1H-G-D9

Solid state relays Model(s) RSSAN-10A, RSSAN-25A, RSSAN-50A, RSSAN-75A, RSSAN-90A, RSSDN-10A, RSSDN-25A, RSSDN-50A, RSSDN-75A, RSSDN-90A

## Investigated to


**Industrial Control Switches** Model(s) RQ1V-CH may be followed by AH or BH, may be followed by -A or -D, may be followed by 6, 12, 24, 48, 60, 110, 115 or 230.

RQ1V-CM may be followed by AM or BM, may be followed by -A or -D, may be followed by 6, 12, 24, 48, 60, 110, 115 or 230.

RQ1V-CN may be followed by AN or BN, may be followed by -A or -D, may be followed by 6, 12, 24, 48, 60, 110, 115 or 230.

RQ2V-CN may be followed by AN or BN, may be followed by -A or -D, may be followed by 6, 12, 24, 46, 48, 110, 115 or 230.

Marking: Company name, model designation and the Recognized Component Mark for Canada, the smallest unit container in which the product is packaged.



Last Updated on 2020-07-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"